

## AMERICAN PLASTIC BOX

<b>MODEL NUMBER</b>	<b>APB1G0W</b>
<b>CUBIC CAPACITY</b>	N/A
<b>DESCRIPTION</b>	Old Work; 1-Gang; Low Voltage Bracket; Swing Bracket.
<b>MATERIAL</b>	PPO
<b>MOUNTING MEANS</b>	Swing Brackets
<b>PRODUCTS SIZE L×W×D</b>	2.52"×4.32"×1.66"
<b>OUTER BOX SIZE L×W×D(CM)</b>	45×33×16
<b>STD. CTN. QTY.</b>	100 Pcs
<b>CERTIFICATIONS</b>	ISO9001, ISO14001, ETL5010519, 2-hour fire rating
<b>COLOR</b>	Various Colors Can Be Customised



Various Colors Can Be Customised

## FEATURES & BENEFITS

- Designed and listed for use with non-metallic sheathed cable in accordance with Article 314 of the National Electrical Code®, they make fast work of any residential or light commercial application.
- Non-metallic boxes feature PPO construction for easier installation, greater performance and lower installation cost.
- All PPO boxes are permissible for use with 90° C connectors.
- Wiring System Non-metallic sheathed cable.
- Various Colors Can Be Customised.
- ETL Listed and carries a 2-hour fire rating.

