

## AMERICAN PLASTIC BOX

|                                     |                                                         |
|-------------------------------------|---------------------------------------------------------|
| <b>MODEL NUMBER</b>                 | <b>PLVP1G</b>                                           |
| <b>CUBIC CAPACITY</b>               | N/A                                                     |
| <b>DESCRIPTION</b>                  | New Work; 1-Gang; Low Voltage Nail-On Mounting Bracket. |
| <b>MATERIAL</b>                     | PPO                                                     |
| <b>MOUNTING MEANS</b>               | Captive Nails                                           |
| <b>PRODUCTS SIZE<br/>L×W×D</b>      | 3.14"×5.34"×1.61"                                       |
| <b>OUTER BOX SIZE<br/>L×W×D(CM)</b> | 41.5×30.5×29                                            |
| <b>STD. CTN. QTY.</b>               | 100 Pcs                                                 |
| <b>CERTIFICATIONS</b>               | ISO9001, ISO14001, ETL5010519, 2-hour fire rating       |
| <b>COLOR</b>                        | Various Colors Can Be Customised                        |



Black

Gray

Various Colors Can Be Customised

## FEATURES & BENEFITS

- Designed and listed for use with non-metallic sheathed cable in accordance with Article 314 of the National Electrical Code®, they make fast work of any residential or light commercial application.
- Non-metallic boxes feature PPO construction for easier installation, greater performance and lower installation cost.
- All PPO boxes are permissible for use with 90° C connectors.
- Wiring System Non-metallic sheathed cable.
- Various Colors Can Be Customised.
- ETL Listed and carries a 2-hour fire rating.

